



# AW-FGT-100P-110

10 Ports Unmanaged PoE Switch



## Technical Specifications

| Product Information    |                        |
|------------------------|------------------------|
| Segment                | Unmanaged PoE Switch   |
| Product Description    | 8xFE PoE + 2xGbE Combo |
| Port Configuration     |                        |
| PoE Port Ethernet      | 8xFE PoE               |
| Uplink Port Ethernet   | 2xGbE Combo            |
| Total Ports            | 10                     |
| PoE Function           |                        |
| PoE Port               | 8                      |
| Max. PoE Output Power  | 30W                    |
| PoE Power Budget       | 110W                   |
| PoE Standard           | 802.3 af/at            |
| PoE Pin Assignment     | 1/2 (+), 3/6 (-)       |
| Surge Protection       | 6KV                    |
| HW Performance         |                        |
| Switching Bandwidth    | 5.6 Gbps               |
| Forwarding Rate        | 1.488 Mpps             |
| MAC Address            | 4K                     |
| Jumbo Frames           | 1,536 Bytes            |
| Max. Power Consumption | 120W                   |
| Surveillance Features  |                        |

|                                   |                                                     |
|-----------------------------------|-----------------------------------------------------|
| Extended Mode (up to 250m/10mbps) | Adaptive<br>>100m with 10Mbps<br><100m with 100Mbps |
| VLAN                              | ✓                                                   |
| Video QoS                         | ✓                                                   |
| PD Alive                          | ✓                                                   |

### Environmental Specifications

|                       |                             |
|-----------------------|-----------------------------|
| Operating Temperature | 0°C ~ 45°C (32°F ~ 113°F)   |
| Storage Temperature   | -20°C ~ 70°C (-4°F ~ 158°F) |
| Operating Humidity    | 10 ~ 90% RH                 |

### Mechanical Specifications

|            |                         |
|------------|-------------------------|
| Dimensions | 270(L) x 181(W) x 44(H) |
| Weight     | 1.2 kg                  |

### Power Source

|             |             |
|-------------|-------------|
| Power Input | 100V ~ 240V |
| Frequency   | 50 ~ 60 Hz  |

### Certifications

|       |                                |
|-------|--------------------------------|
| Types | CE, FCC, UKCA, LVD, VCCI, BSMI |
|-------|--------------------------------|

### Included Accessories

|         |                                 |
|---------|---------------------------------|
| Content | Power Cord, QIG, Rack Mount Kit |
|---------|---------------------------------|