



IB9380-H

Bullet Network Camera



5MP • SNV • WDR Pro • Smart IR • 30M IR •
Smart Stream III • IP66

VIVOTEK's IB9380-H is a H.265 outdoor bullet network camera equipped with a 5-Megapixel sensor, enabling resolution of 2560x1920 at 20 fps. Featuring VIVOTEK SNV and WDR Pro technology, the IB9380-H is capable of capturing high-quality imagery in both high contrast and low light environments.

The IB9380-H deploys a 3.6mm lens and is equipped with IR illuminators with a 30-meter effective range for better night visibility. Further, to provide reliable coverage in harsh outdoor environments, the IB9380-H is encased in IP66 and IK10 housing.

By employing VIVOTEK's Smart Stream III technology and H.265 codec support, the IB9380-H is able to reduce bandwidth usage by up to 90%* while maintaining supreme image quality. Additionally, the VADP (VIVOTEK Application Development Platform) allows users to customize applications for the ever-expanding number of user scenarios in a diversifying surveillance market.

* Depending on scenes


Key Features

- H.265 Compression Technology
- 20 fps @ 2560x1920 (WDR Pro on)
- SNV (Supreme Night Visibility) for Low Light Conditions
- WDR Pro for Unparalleled Visibility in Extremely Bright and Dark Environments
- Smart Stream III to Optimize Bandwidth Efficiency
- Built-in IR Illuminators, Effective up to 30 Meters
- Trend Micro IoT Security
- Weather-proof IP66-rated and Vandal-proof IK10-rated Housing
- Built-in MicroSD/SDHC/SDXC Card Slot for On-board Storage



Without WDR Pro

With WDR Pro



H.265 + Smart Stream III, Ultra-low Bandwidth

Technical Specifications

Model	IB9380-H	
System Information		
CPU	Multimedia SoC (System-on-Chip)	
Flash	128MB	
RAM	512MB	
Camera Features		
Image Sensor	1/2.7" Progressive CMOS	
Max. Resolution	2560x1920 (5MP)	
Lens Type	Fixed-focal	
Focal Length	f = 3.6 mm	
Aperture	F2.0	
Iris type	Fixed-iris	
Field of View	76° (Horizontal) 59° (Vertical) 100° (Diagonal)	
Shutter Time	1/5 sec. to 1/32,000 sec.	
WDR Technology	WDR Pro	
Day/Night	Yes	
Removable IR-cut filter	Yes	
IR Illuminators	Built-in IR Illuminators up to 30 meters with Smart IR, IR LED*2	
Minimum Illumination	0.03 lux @ F2.0 (Color) <0.005 lux @ F2.0 (B/W) 0 Lux with IR illumination on	
Tilt Range	90°	
Rotation Range	180°	
Pan/Tilt/Zoom Functionalities	ePTZ: 48x digital zoom (4x on IE plug-in, 12x built-in)	
On-board Storage	Slot type: MicroSD/SDHC/SDXC card slot Seamless Recording	
Video		
Compression	H.265, H.264, MJPEG	
Maximum Frame Rate	20 fps @ 2560x1920	
Maximum Streams	3 simultaneous streams	
S/N Ratio	67 dB	
Dynamic Range	120 dB	
Video Streaming	Adjustable resolution, quality and bitrate, Smart Stream III	
Image Settings	Time stamp, text overlay, flip & mirror; Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks; Scheduled profile settings, HLC, defog, 3DNR, video rotation	
Network		
Users	Live viewing for up to 10 clients	
Protocols	802.1X, ARP, CIFS/SMB, CoS, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMP, IPv4, IPv6, NTP, PPPoE, QoS, RTSP/RTP/RTCP, SMTP, SNMP, SSL, TCP/IP, TLS, UDP, UPnP	
Interface	10 Base-T/100 Base-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.	
ONVIF	Supported, specification available at www.onvif.org	
Intelligent Video		
Video Motion Detection	Five-window video motion detection	
VADP Package	Trend Micro IoT Security, Stratocast	
Alarm and Event		
Alarm Triggers	Motion detection, periodical trigger, system boot, recording notification, camera tampering detection, temperature detection, manual trigger, SD card life expectancy, cybersecurity events (brute force attack event, cyberattack event, quarantine event)	
Alarm Events	Event notification via email, HTTP, FTP, NAS server, SD card File upload via email, HTTP, FTP, NAS server, SD card	
General		
Connectors	RJ-45 cable connector for Network 10/100 Mbps PoE connection*1	
LED Indicator	System power and status indicator	
Power Input	IEEE 802.3af PoE Class 2	
Power Consumption	Max. 6.49 W (IR on) Max. 3.6 W (IR off)	
Dimensions	Ø 91.1 x 176.8 mm	
Weight	530 g	
Casing	IP66, IK10(Housing)	
Safety Certifications	CE, FCC Class B, UL, LVD, VCCI, C-Tick	
Operating Temperature	Starting Temperature: -10°C ~ 60°C (14°F ~ 140°F) Working Temperature: -30°C ~ 60°C (-22°F ~ 140°F)	
Humidity	98%	
Warranty	24 months	
System Requirements		
Operating System	Microsoft Windows 8/7 Mac 10.12 (Chrome only)	
Web Browser	Chrome 58.0 or above Internet Explorer 10/11	


Technical Specifications

Other Players VLC: 1.1.11 or above
QuickTime: 7 or above

Included Accessories

Others Quick installation guide, alignment sticker,
screw pack, cable gland

Dimensions



Compatible Accessories

Mounting Kits



AM-312
Pole Mount Adapter



AM-412
Corner Mount Adapter



AM-523
Adapting Plate